

Please do not change any of the values in this sheet

Patm	Atmospheric air pressure - (As recorded from engine data)	980 [mBar]
Patm		98000 [Pa]
Tatm		15 [C]
Tatm		288 [K]
Relative Humidity		65 [%]

$$\rho_{\text{humid air}}^{[1]} = \frac{p_d}{R_d T} + \frac{p_v}{R_v T} = \frac{p_d M_d + p_v M_v}{R T}$$

where:

$\rho_{\text{humid air}}$	=	Density of the humid air (kg/m <sup>3</sup> )	$\rho_{\text{humid air}}$	=	1.180379 Kg/m <sup>3</sup>
$p_d$	=	Partial pressure of dry air (Pa)			
$R_d$	=	Specific gas constant for dry air, 287.058 J/(kg·K)			
$T$	=	Temperature (K)		0.425142855	
$p_v$	=	Pressure of water vapor (Pa)			
$R_v$	=	Specific gas constant for water vapor, 461.495 J/(kg·K)			
$M_d$	=	Molar mass of dry air, 0.028964 (kg/mol)			
$M_v$	=	Molar mass of water vapor, 0.018016 (kg/mol)			
$R$	=	<a href="#">Universal gas constant, 8.314 J/(K·mol)</a>			

The vapor pressure of water may be calculated from the saturation vapor pressure and relative humidity. It is found by:

$$p_v = \phi p_{\text{sat}}$$

$p_v = 1108.398 \text{ [Pa]}$

Where:

$p_v$	=	Vapor pressure of water
$\phi$	=	Relative humidity
$p_{\text{sat}}$	=	Saturation vapor pressure

The saturation vapor pressure of water at any given temperature is the vapor pressure when relative humidity is 100%. One formula<sup>[1]</sup> used to find the saturation vapor pressure is:

$$p_{\text{sat}} = 6.1078 \times 10^7 \frac{e^{-\frac{1764}{T-30.56}}}{T^2}$$

$p_{\text{sat}} = 17.05228 \text{ hPa}$   
 $p_{\text{sat}} = 1705.228 \text{ [Pa]}$

where T is in degrees C. Note:

This will give a result in hPa (100 Pa, equivalent to the older unit millibar, 1 mbar = 0.001 bar = 0.1 kPa)

$p_d$  is found considering partial pressure, resulting in:

$$p_d = p - p_v$$

$p_d = 96891.6 \text{ [Pa]}$

Where p simply denotes the observed absolute pressure.

$$\rho = \frac{p}{R_{\text{specific}} T} \quad 1.1854 \text{ [kg/m}^3\text{]}$$

R = 287.058 J/Kg K  
T = Temperature in degrees Kelvin  
P = Absolute Pressure in Pa