

Please do not change any of the values in this sheet

Patm	Atmpnspheric air pressure - (As recorded from engine data)	967.1 [mBar]
Patm		96710 [Pa]
Tatm		22.1 [C]
Tatm		295.1 [K]
Relative Humidity		40 [%]

$$\rho_{\text{humid air}}^{[1]} = \frac{p_d}{R_d T} + \frac{p_v}{R_v T} = \frac{p_d M_d + p_v M_v}{R T}$$

where:

$\rho_{\text{humid air}}$	=	Density of the humid air (kg/m ³)
p_d	=	Partial pressure of dry air (Pa)
R_d	=	Specific gas constant for dry air, 287.058 J/(kg·K)
T	=	Temperature (K)
p_v	=	Pressure of water vapor (Pa)
R_v	=	Specific gas constant for water vapor, 461.495 J/(kg·K)
M_d	=	Molar mass of dry air, 0.028964 (kg/mol)
M_v	=	Molar mass of water vapor, 0.018016 (kg/mol)
R	=	Universal gas constant, 8.314 J/(K·mol)

$$\rho_{\text{humid air}} = 1.13695 \text{ Kg/m}^3$$

$$0.41337253$$

The vapor pressure of water may be calculated from the saturation vapor pressure and relative humidity. It is found by:

$$p_v = \phi p_{\text{sat}}$$

$$p_u = 1063.95 \text{ [Pa]}$$

Where:

p_v	=	Vapor pressure of water
ϕ	=	Relative humidity
p_{sat}	=	Saturation vapor pressure

The saturation vapor pressure of water at any given temperature is the vapor pressure when relative humidity is 100%. One formula^[1] used to find the saturation vapor pressure is:

$$p_{\text{sat}} = 6.1078 \times 10^7 \exp\left(\frac{17.3}{273.15 - T}\right)$$

$$p_{\text{sat}} = 26.5986 \text{ hPa}$$

$$p_{\text{sat}} = 2659.86 \text{ [Pa]}$$

where T is in degrees C. Note:

This will give a result in hPa (100 Pa, equivalent to the older unit millibar, 1 mbar = 0.001 bar = 0.1 kPa)

p_d is found considering partial pressure, resulting in:

$$p_d = p - p_v$$

$$p_d = 95646.1 \text{ [Pa]}$$

[Where p simply denotes the observed absolute pressure.](#)

$$\rho = \frac{p}{R_{\text{specific}} T} \quad 1.14165 \text{ [kg/m}^3]$$

$$R = 287.058 \text{ J/Kg K}$$

$$T = \text{Temperature in degrees Kelvin}$$

$$P = \text{Absolute Pressure in Pa}$$